

[Louis A Green Corp](#)

**Weldable Webbing**

(800) 225-3577

Substrate Webbing (Scrim): 100% Polyester.  
Impregnated Coating: Polyvinyl Chloride (PVC).  
Non-Wicking.

<u>Part Number</u>	<u>Width mm.</u>	<u>Width in.</u>	<u>Nominal Width in.</u>	<u>Standard Colors</u>	<u>Thickness (mm)</u>	<u>in.</u>	<u>Tensile kgs.</u>	<u>Tensile lbs.</u>	<u>Weight gr/m</u>	<u>Weight oz/yd.</u>
--------------------	------------------	------------------	--------------------------	------------------------	-----------------------	------------	---------------------	---------------------	--------------------	----------------------

**Lighter Weight and Standard Products**

1281-25	25	1"	1	white	1.00	3/64"	700	1400	24	0.8
1281-1	30	1-3/16"	1	white	1.00	3/64"	750	1650	28	1.0
1281-2	47	1-7/8"	2	white black gray	1.00	3/64"	1300	2900	49	1.6
7007	47	1-7/8"	2	black	1.60	1/16"	2400	5200	78	2.5
7010	50	2"	2	white	1.65	1/16"	2800	5900	83	2.9

**Heavier Weight and Specialty Products\***

(in ascending order by tensile strength)

4630	25	1"	1	white black	1.80	5/64"	2000	4400	50	1.8
5052-628	28	1-1/8"	1	white	2.50	3/32"	3000	6600	90	3.2
4763-99	30	1-3/16"	1	white	3.30	1/8"	4500	9900	105	3.7
5052-110	50	2"	2	white	2.25	5/64"	5000	11000	133	4.7
4763-165	50	2"	2	white	3.30	1/8"	7500	16500	179	6.3

\* Consult manufacturer concerning machine settings for welding thicker materials.

[Back to Weldable Web page](#)